

## FORESTRY MULCHERS FOR EXCAVATORS

# BL1/EX - BL1/EX/VT

Forestry mulcher with Bite Limiter technology.



50-140 L/min



Ø 12 cm max



4-7,5 t

### STANDARD EQUIPMENT

17/34cc variable manual displacement hydraulic piston motor with relief and anticavitation valve (50-130 L/min) (BL1/EX)	Motor enclosed in the frame
55/38cc variable torque hydraulic piston motor (65-140 L/min) (BL1/EX/VT)	Belt transmission
Flow control system valve	Bulkhead for hydraulic connections
Safety and anticavitation valve	Front hood with mechanical adjustment
Enclosed / anti dust machine body	Rotor Bite Limiter

### OPTIONS

Customized setting hydraulic motor	Dedicated rear hood (deflector)
Diverter valve (plug & play)	Front fixed thumb bracked
Hydraulic front hood	Customized attachment bracket with pins
Hydraulic front hood for excavator AUX line	Multiple tooth options

MODEL	BL1/EX-75	BL1/EX/VT-75
<b>Flow rate</b> (L/min)	50-130	65-140
<b>Pressure</b> (bar)	180-350	180-350
<b>Excavator weight</b> (t)	4-7,5	4-7,5
<b>Working width</b> (mm)	800	800
<b>Weight</b> (Kg)	355	355
<b>Rotor diameter</b> (mm)	300	300
<b>Max shredding diameter</b> (mm)	120	120
<b>No. blades</b> type MINI BL	14	14

Data refers to machine as standard. The technical data in this catalogue may be altered without prior notice.



**Blade MINI BL**  
(standard)



**MINI C/3**  
(option)